


MISSOURI STATE HIGHWAY DEPARTMENT



FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	73	



		1	2	3 S.B.	3 N.B.	4 S.B.	4 N.B.
SPREAD FOOTINGS	Foundation Material		Rock or Shale				
	Design Bearing Tons/sq.ft.		9.0	8.8			
BEARING PILE	Pile Type & Size	10BP42			10BP42	10BP42	
	Number	13			12	18	
	Approximate Length Ft.	17			22	32	17
	Design Bearing Value Tons	56			51	54	
Hammer Energy Req'd. #13,700					12,000	12,200	

Note: \* Minimum energy requirement of hammer based on plan length and design bearing value of piles. Increase by the factor (W+w)/2W when the weight of the ram (W) is less than the weight of the pile (w). All pile shall be driven to practical refusal. In no case shall footings of Int. Bents be placed higher than elevation 958.0 shown.

Note: Compacted roadway fill (Full roadway width) shall be placed up to elevation of bottom of concrete beam in front of and not less than 25'-0" in back of all End Bents except End Bent 1 S.B.L. before steel piles are driven.



GENERAL NOTES:  
 Design Specifications: A.A.S.H.O. - 1961  
 Design Loading: HS20-44  
 15"/sq.ft. Future Wearing Surface Modified 24,000# Tandem Axle Earth 120# Equivalent Fluid Pressure 30"  
 Design Unit Stresses:  
 Class B Concrete (substructure)  $f_c = 1,200$  psi  
 Class B1 Concrete (superstructure)  $f_c = 1,600$  psi  
 Reinforcing Steel  $f_s = 20,000$  psi  
 Structural Steel (A.S.T.M. A36 - C2T)  $f_s = 20,000$  psi  
 Steel Pile (A.S.T.M. A36 - C2T)  $f_s = 9,000$  psi  
 Superstructure deck to be surface scaled.  
 Field connections, High Strength Bolts  $\frac{3}{4}" \phi$ , hole  $\frac{1}{2}" \phi$  except as noted.  
 Paint; shop, none; Field, three coats.

ITEM	SUBSTR.	SUPERSTR.	TOTAL
Class I Excavation for Structures	Cu.Yds	170	170
Steel Piles in Place (10')	Lin.Ft.	1281	1281
Class B Concrete	Cu.Yds	317.0	317.0
Class B1 Concrete	Cu.Yds	524.7	524.7
Reinforcing Steel	Lbs	49,720	72,450
Painting	Tons	187.0	187.0
Fabricated Structural Carbon Steel	Lbs	378,400	378,400
Bridge Rail (Single Tube Type)	Lin.Ft.	358	358
Guard Rail Type B (Steel) (Bolt Down)	Lin.Ft.	130	160

Note: Concrete in end posts, parapets and curbs is included with superstructure concrete.  
 No payment for excavation will be allowed at End Bents 1 and 4.

For Boring Data see Sheet 2.  
 \* Indicates location of boring.

M - Elev. 973.54 - 3 Nails in N. Side R.R. 130' Rt. Sta. 828+60 Rt. Lane I-29.

SUBMITTED BY E. LYN CROWLEY  
 SIGNATURE E. Lyn Crowley  
 REGISTERED PROFESSIONAL ENGINEER  
 SERIAL NUMBER E-5893



**BRIDGE OVER ROUTE 45**  
 STATE ROAD - INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. 1-29-1(36) (RTE. 1-29) STA. 828+24.26 & MEDIAN  
 PLATTE COUNTY

SUBMITTED BY: [Signature] DATE: 3-29-66  
 APPROVED BY: [Signature] DATE: 3-29-66

STD 54.00
STD. 86.00
A-1159

PRICHARD COMPANY, INC.  
 CONSULTING ENGINEERS  
 INDEPENDENCE, MISSOURI  
 DESIGNED JAN. 1966 BY P.H.R.  
 DETAILED JAN. 1966 BY R.M.F.  
 CHECKED FEB. 1966 BY E.D.F.

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1 of 14.

SEE FINAL PLANS DRAWN-LINES








290



MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	77	

Note: For curb and end post reinforcing see Sheet 14.



Note: Fill at end bents 1 and 4 shall not be carried above bottom of beam and wings until adjacent superstructure spans is in place.  
 Top of backwall and expansion device for end bent 4 to conform to crown of roadway slab.  
 Dimensions and Elevations marked \* are at the Fill Face.

292

BRIDGE OVER ROUTE 45  
 STATE ROAD - INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. 1-29-1C5 (RTE. 1-29) STA. 828+24.26 & MEDIAN  
 PLATTE COUNTY

DETAILED FEB. 1966 BY H.H.B.  
 CHECKED FEB. 1966 BY J.E.R.

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 3 of 14.

A-1159

NO CONSTRUCTION DETAILS






MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	20	

Note: For curb and end post reinforcing see Sheet 14.



Note: For steel pile splice detail and end bent notes see Sheet 3. Dimensions and Elevations marked \* are at the Fill Face.

295

DETAILED FEB. 1966 BY N.H.B.  
CHECKED FEB. 1966 BY R.D.F.

Note: This drawing is not to scale. Follow dimensions.

DETAILS OF END BENT-4 N.B. LANE

Sheet No. 6 of 14.


BRIDGE OVER ROUTE 45  
STATE ROAD - INTERSTATE ROUTE 29  
IN KANSAS CITY  
PROJECT NO. I-29-1136 (RTE. 1-29) STA. 828+24.26 & MEDIAN  
PLATTE COUNTY

A-1159

NO CONSTRUCTION CHANGES

MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PRO. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	81	



Note: For curb and end post reinforcing see Sheet 14.

Note: For steel pile splice detail and end bent notes see Sheet 3. Dimensions and Elevations marked \* are at the Fill Face.

296

DETAILED FEB. 1966 BY H.H.B.  
CHECKED FEB. 1966 BY J.E.R.

Note: This drawing is not to scale. Follow dimensions.

DETAILS OF END BENT - 4 S.B. LANE

Sheet No. 7 of 14.


BRIDGE OVER ROUTE 45  
STATE ROAD - INTERSTATE ROUTE 29  
IN KANSAS CITY  
PROJECT NO. I-29-1(36)(RTE. I-29) STA. 828+24.26 & MEDIAN  
PLATTE COUNTY

A-1159

XX







FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	87	

MISSOURI STATE HIGHWAY DEPARTMENT



PLAN OF STRUCTURAL STEEL  
N.B. Lane shown S.B. Lane similar

Note: Longitudinal dimensions shown are taken parallel to grade at crown of roadway.



① Groove weld penetration - 1/4" Min. Only welding processes having good penetration will be permitted on groove welds.

Note: This drawing is not to scale. Follow dimensions.

297

DETAILED JAN. 1963 BY H.M.B.  
CHECKED FEB. 1963 BY E.D.F.

Sheet No. 3 of 14.

NO CONSTRUCTION CHANGES


BRIDGE OVER ROUTE 45  
STATE ROAD - INTERSTATE ROUTE 29  
IN KANSAS CITY  
PROJECT NO. 1-29-136 (RTE. 1-29) STA. 828+24.26 & MEDIAN  
PLATTE COUNTY

A-1159






MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	84	



Note: Min. Lap for #4 bar is 12".  
" " " #6 " " 18".

PART PLAN OF SLAB SHOWING REINFORCING STEEL  
N.B. LANE SHOWN (S.B. Lane Similar except for Longitudinal Const. Jt. location)





Note: Longitudinal Reinforcing Steel shall be placed so that ends shall not be more than 1 1/2" from 3/8" plate at Expansion Device.

DEAD LOAD DEFLECTION  
Note: 12.6% of dead load deflection is due to weight of structural steel.

Sequence of Pours	Direction		
	1	2	3
Basic Sequence	End to 2	1 to 3	2 to End
Alternate A Pours	1 + 2		3
Alternate B Pours	End to 3	2 to End	
Alternate B' Pours	1 + 2 + 3		
	End to End		

Note: The contractor shall use an approved oscillating screed type, self-propelled mechanical finishing machine and shall pour and satisfactorily finish the slab pours at a rate of not less than 40 cubic yards per hour unless he elects to use an approved retarder at his own expense to retard the set of the concrete to 2.5 hours in which case he may reduce his pouring and finishing rate to not less than 25 cubic yards per hour. The contractor shall observe the basic pouring sequence unless he can demonstrate to the engineer that he can pour and satisfactorily finish one of the longer alternate pours. Finishing machine loads will not be permitted on concrete less than 48 hours old.



BRIDGE OVER ROUTE 45  
STATE ROAD-INTERSTATE ROUTE 29  
IN KANSAS CITY  
PROJECT NO. I-29-136 (RTE. I-29) STA. 828+24.26 ± MEDIAN  
PLATTE COUNTY

662

DETAILED JAN. 1966 BY RWF  
CHECKED FEB. 1966 BY JER

SLAB POURING SEQUENCE

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 10 of 14. Revised 4-4-67


A-1159

NO CONSTRUCTION CHANGES



MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	86	



NOTES: TYPE "C" BEARINGS  
Anchor Bolts for Type "C" Bearings shall be 1"  $\phi$  swaged bolts, 10" long with no heads or nuts. Top of Anchor Bolts shall be set approximately 1/4" below top of bearing.

NOTES: TYPE "D" BEARINGS  
Anchor Bolts for Type "D" Bearings shall be 1 1/2"  $\phi$  swaged bolts and shall extend 12" into concrete, with hexagon nuts and plain washers for Fixed Bearings, no nuts for Expansion Bearings. Rockers and pedestals shall be machined after welding.

GENERAL NOTES:  
Lead Plates under bearings shall be approximately 3/8" thickness and weigh 8#/sq. ft. Cost of lead plates shall be included in price bid for other items.  
"Estimated Weight" does not include weight of anchor bolts.

Where flat surface is indicated, tolerance shall be .003 in/in in any direction.

BRIDGE OVER ROUTE 45  
STATE ROAD - INTERSTATE ROUTE 29  
IN KANSAS CITY  
PROJECT NO. I-29-106 (RTE. 1-29) STA. 828+24.26  $\pm$  MEDIAN  
PLATTE COUNTY

No. 4.1 Revised Dec. 1961 Feb. 1965

301

DETAILED JAN. 1966 BY H.H.S.  
CHECKED FEB. 1966 BY F.D.F.

Note: This drawing is not to scale. Follow dimensions.





Sheet No. 12 of 14.

NO CONSTRUCTION CHANGES

A-1159



MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	27	




Note: See Standard 86.00 for Details of Blocked Out Post, Rail and Buffer Ends.

DETAILS OF TYPE B GUARD RAIL (BOLT DOWN)



GENERAL NOTES:  
 All other details not shown shall comply with Std. 86.00  
 Grout shall comply with Std. Specs. Sec. 166.1.5.  
 Tightening of nuts on bolts connecting rail members and posts shall be to the extent that longitudinal movement of the bolt in slotted holes is possible. After tightening in this manner the top of the bolt shall be deformed in such a way as to prevent loss of nut.  
 Guard Rail Posts shall be set normal to grade.  
 Buffer End for Type B Guardrail will be required at each end of bridge.  
 All bridge guardrail shall be cleaned and painted in the field or may be cleaned and painted one coat of red lead in the shop with the two remaining coats applied in the field. In lieu of painting, the contractor may, if he prefers, galvanize this material. All galvanizing shall be done after fabrication. Cost of painting or galvanizing to be included in price bid for other items.



BRIDGE OVER ROUTE 45  
 STATE ROAD - INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. I-29-1-CO (SEC. A) (RTE. 1-29) STA. 828+24.26 E. MEDIAN  
 PLATTE COUNTY

302  
 DETAILED JAN. 1966 BY H.H.B.  
 CHECKED FEB. 1966 BY J.E.R.

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 13 of 14.

A-1159





SEE FINAL PLANS FOR BROWNS LINES

FED ROAD DIST NO	STATE	FED AID PROJ NO	FISCAL YEAR	SHEET NO	TOTAL SHEETS
5	MO.		'9	98	

**GENERAL NOTES:**

All handrail posts shall be set normal to grade.  
 Aluminum tube handrail shall be bent to conform to vertical and horizontal alignment of parapet.  
 Aluminum washer shims between top of parapet and post base may be used for adjusting handrail alignment. Maximum thickness of shims to be 1/8". Where more tilting of post is required for proper alignment, concrete bearing areas shall be ground down.  
 All parts of handrail, except anchor bolts, nuts, washers, and set screws are to be of aluminum material.  
 The contract unit price per linear foot of "Bridge Rail" shall include furnishing and erecting the handrail complete with anchor bolts, shims and insulating compound.  
 All fillets 1/4" except as noted.  
 All drafts 3° except as noted.  
 Pipe rail to be fabricated in two or three panel lengths unless otherwise approved.  
 Omit set screw on side near filled joint in parapet at all expansion posts.  
 Top of curbs and parapets to be built parallel to grade with curb and parapet joints (except at end posts), normal to grade.  
 Concrete end posts to be vertical.  
 All exposed edges of end posts, parapets and curbs shall have 1/2" radius.  
 If the contractor desires, he may use drive fit cast aluminum end caps in lieu of welded aluminum closure plates.  
 Integrally cast test coupons and a coat of clear lacquer specified in Std. Spec. 56.2.4 and 56.3.5 respectively will not be required for these rail posts.


**MISSOURI STATE HIGHWAY DEPARTMENT**



Note: Anchor bolts for attaching guard rail shall be 1/2" threaded (Galv.) inserts having a minimum depth of 4" and filled with a plastic closing plug. Cost for furnishing and installing the insert and plug will be included in price bid for other items.

REINFORCING		
SPAN (1-2)	(2-3)	(3-4)
#5-C4 (2-Units)	#5-C5 (3-Units)	#5-C6 (2-Units)
#5-R8 (2-Units)	#5-R9 (2-Units)	#5-R10 (2-Units)

Note: For horizontal curb and parapet bars use minimum lap of 15" for #5.



Note: Plastic waterstop shall be placed in all parapet and curb filled joints. (Except at End Jts) cost of plastic waterstop complete in place to be included in unit price bid for concrete.  
 DETAILS OF PLASTIC WATER STOP

**BRIDGE OVER ROUTE 45**  
 STATE ROAD - INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. 1-29-106 (SEC. A) STA. 828+24.26 & MEDIAN  
 PLATTE COUNTY

303

No. 1.5.2 A Revised Nov 1963 Oct 1963

DETAILED JAN. 1966 BY H.H.B.  
 CHECKED FEB. 1966 BY J.E.R.


Note: This drawing is not to scale. Follow dimensions.

Sheet No. 14 of 14

A-1159


MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	73	




SPREAD FOOTINGS	BENT NO.			
	1	2	3	4
Foundation Material	---	Rock or Shale	---	---
Design Bearing Tons/sq.ft.	---	9.0	8.8	---
BEARING PILE	Pile Type & Size Number	103P42 13	103P42 12	103P42 18
	Approximate Length Ft.	17	22	32
	Design Bearing Value Tons	56	51	47
	Hammer Energy Req'd. #13,700	---	12,000	12,200

Note: \* Minimum energy requirement of hammer based on plan length and design bearing value of piles. Increase by the factor (W+w)/2W when the weight of the ram (W) is less than the weight of the pile (w).  
 All pile driven to practical refusal.  
 In no case were footings of Int. Bents placed higher than elevation 958.0 shown.



Note: Compacted roadway fill (full roadway width) was placed up to elevation of bottom of concrete beam in front of and not less than 25'-0" in back of all End Bents except End Bent 1 S.B.L. before steel piles were driven.



GENERAL NOTES:  
 Design Specifications: A.A.S.H.O. - 1961  
 Design Loading: HS20-44  
 15"/sq.ft. Future Wearing Surface Modified 24,000# Tandem Axle Earth 120# Equivalent Fluid Pressure 30#  
 Design Unit Stresses:  
 Class B Concrete (substructure)  $f_c = 1,200$  psi  
 Class BI Concrete (superstructure)  $f_c = 1,600$  psi  
 Reinforcing Steel  $f_s = 20,000$  psi  
 Structural Steel (A.S.T.M. A36-G2T)  $f_s = 20,000$  psi  
 Steel Pile (A.S.T.M. A36-G2T)  $f_b = 9,000$  psi  
 Superstructure deck surface sealed.  
 Field connections, High Strength Bolts 3/4", holes 1/2" except as noted.  
 Paint; shop, none; Field, three coats.

ITEM	SUBSTR.	SUPERSTR.	TOTAL
Class I Excavation for Structures	Cu Yds	204.0	204.0
Steel Piles in Place (10)	Lin. Ft.	1,350	1,350
Class B Concrete	Cu Yds	319.4	319.4
Class BI Concrete	Cu Yds	524.7	524.7
Reinforcing Steel	Lbs	174,730	224,820
Painting	Tons	186.0	186.0
Fabricated Structural Carbon Steel	Lbs	376,630	376,630
Bridge Rail (Single Tube Type)	Lin. Ft.	355	355
GR-B-Bolt Down 6-35P	Lin. Ft.	180	180
Class I Exc. + 25%	Cu. Yds	22.0	22.0
Drilled Test Holes	Lin. Ft.	42	42

For Boring Data see Sheet 2.  
 \* Indicates location of boring.  
 Round Headed Bolt in curb @ F.F. Bt. No. 1 Rt. Elev. 984.83  
 Round Headed Bolt in curb @ F.F. Bt. No. 4 Lt. Elev. 981.63

SUBMITTED BY E. LYN CROWLEY  
 SIGNATURE E. Lyn Crowley  
 REGISTERED PROFESSIONAL ENGINEER  
 SERIAL NUMBER E-5993

Note: Concrete in end posts, parapets and curbs is included with superstructure concrete. No payment for excavation allowed at End Bents 1 and 4.  
**BRIDGE OVER ROUTE 45**  
 STATE ROAD - INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. I-29-1(36) (RTE. I-29) STA. 828+24.26 & MEDIAN  
 PLATTE COUNTY

PRICHARD COMPANY INC.  
 CONSULTING ENGINEERS  
 INDEPENDENCE, MISSOURI  
 DESIGNED JAN. 1966 BY R.H.A.  
 DETAILED JAN. 1966 BY R.M.F.  
 CHECKED FEB. 19 BY F.D.F.

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1A of 5  
 FINAL PLANS

APPROVED BY M.J. Snider  
 CHIEF ENGINEER  
 DATE 3-24-66  
 STD 24.00  
 STD 86.00  
 A-1159

304


MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	76	

FINAL PLANS

COMPLETE BILL OF REINFORCING STEEL

NO. SIZE LENGTH MARK LOCATION				BENDING SKETCHES & CUTTING DIAGRAMS				NO. SIZE LENGTH MARK LOCATION							
SUPERSTRUCTURE								SUBSTR. INT. BENTS 2 & 3							
NBL.	SBL.							NBL.	SBL.						
40	#5	3'-3"	C1	20	20	[Bending sketches for bars 40-49]				16	#10	25'-0"	G1	8	8
3	#6	9'-6"	C2	4	4					12	#10	14'-0"	G2	6	6
360	#5	3'-6"	C3	180	180					16	#11	36'-6"	G3	8	8
8	#5	27'-0"	C4	4	4					16	#11	15'-6"	G4	8	8
12	#5	26'-6"	C5	6	6					16	#7	13'-9"	G5	3	3
8	#5	25'-0"	C6	4	4					32	#11	29'-3"	G6	16	16
183	#4	10'-6"	C7	183						32	#11	20'-0"	G7	16	16
390	#5	11'-3"	C8	390						32	#6	28'-6"	G8	16	16
362	#4	2'-3"	C9	362						32	#7	6'-6"	G9	16	16
14	#4	29'-3"	C10	14						100	#6	12'-9"	U7	50	50
14	#4	2'-6"	C11	14						48	#4	3'-9"	U10	24	24
30	#5	29'-3"	C12	30						8	#4	3'-3"	U11	4	4
21	#4	26'-3"	C13	21						96	#9	5'-0"	D1	48	48
75	#5	26'-6"	C14	75						48	#2	19'-9"	W1	24	24
24	#5	9'-3"	R1	12	12					SUBSTR. INT. BENT 2					
4	#5	5'-9"	R2	2	2					98	#3	8'-0"	P1	61	45
4	#5	6'-9"	R3	2	2					8	#9	25'-0"	P2	8	8
4	#5	7'-0"	R4	2	2					24	#9	27'-6"	P3	16	8
4	#5	7'-3"	R5	2	2					16	#9	10'-3"	P6	16	16
24	#5	7'-6"	R6	12	12					55	#6	13'-3"	U8	55	
360	#5	5'-6"	R7	180	180					55	#6	13'-6"	U9		55
16	#5	22'-9"	R8	8	8					36	#5	4'-0"	D2	18	18
16	#5	30'-0"	R9	8	8					26	#5	7'-0"	D4	19	8
16	#5	20'-6"	R10	8	8					18	#5	6'-3"	D5	6	12
32	#5	8'-6"	R11	16	16					SUBSTR. INT. BENT 3					
2576	#6	26'-6"	S1	1288	1288					108	#3	8'-0"	P1	39	69
136	#6	29'-9"	S2	68	68					8	#9	15'-9"	P4	8	
132	#6	28'-3"	S3	66	66					16	#9	16'-0"	P5	16	
624	#4	31'-0"	S4	312	312					8	#9	27'-9"	P7	3	
204	#4	16'-0"	S5	102	102					16	#9	25'-0"	P8	16	
510	#6	37'-3"	S6	255	255					55	#6	13'-3"	U8	55	
8	#4	31'-6"	S7	4	4					55	#6	13'-6"	U9		55
SUBSTRUCTURE END BENT 1				NBL.	SBL.					18	#5	4'-0"	D2	18	18
6	#5	5'-0"	A1	6	6					24	#6	7'-0"	D3	24	14
6	#5	7'-6"	A2	6	6					14	#5	7'-0"	D4	14	14
4	#8	44'-9"	H1	4	4					9	#5	7'-3"	D6	9	9
8	#8	36'-0"	H2	8	8					SUBSTRUCTURE END BENT 4					
4	#8	27'-0"	H3	4	4					8	#8	36'-0"	H2	8	8
4	#6	34'-9"	H4	4	4					4	#6	34'-9"	H4	4	4
8	#6	33'-9"	H5	4	4					24	#4	33'-6"	H6	12	12
16	#4	33'-6"	H6	8	8					2	#4	4'-0"	H7	2	2
2	#4	4'-0"	H7	2	2					1	#6	9'-9"	H8	2	2
4	#6	9'-9"	H8	2	2					4	#6	9'-0"	H9	2	2
4	#6	9'-0"	H9	2	2					4	#6	7'-0"	H10	2	2
4	#6	7'-0"	H10	2	2					4	#6	5'-6"	H11	4	4
4	#6	5'-6"	H11	4	4					3	#4	9'-3"	H12	3	3
3	#4	9'-3"	H12	3	3					8	#8	34'-3"	H14	8	8
4	#8	30'-3"	H13	4	4					4	#6	33'-0"	H16	4	4
8	#8	34'-3"	H14	8	8					4	#6	8'-3"	H18	4	4
4	#8	35'-3"	H15	4	4					4	#4	6'-6"	H19	4	4
4	#6	3'-0"	H16	4	4					8	#6	31'-9"	H20	4	4
2	#4	3'-0"	H17	2	2					4	#8	12'-6"	H21	4	4
4	#6	8'-5"	H18	4	4					4	#8	26'-0"	H22	4	4
3	#4	6'-6"	H19	3	3					4	#8	37'-0"	H23	4	4
2	#6	9'-3"	T1	2	2					4	#8	34'-6"	H24	4	4
2	#6	9'-9"	T2	2	2					2	#4	5'-0"	H26	2	2
47	#5	12'-5"	U1	22	25					2	#6	9'-6"	T3	2	2
43	#5	13'-0"	U2	43						2	#6	9'-3"	T4	2	2
33	#5	13'-3"	U3	33						40	#5	12'-3"	U1	21	28
12	#4	3'-0"	U4	5	7					37	#5	13'-0"	U2	37	37
4	#4	3'-9"	U5	14	14					37	#5	13'-3"	U3	37	37
1	#4	3'-9"	U6	11	11					14	#4	3'-9"	U4	6	8
2	#5	3'-9"	V1	122	122					12	#4	3'-9"	U5	12	12
15	#2	5'-6"	V2	10	8					11	#4	3'-9"	U6	11	11
16	#4	6'-9"	V3	8	8					16	#4	6'-9"	V3	8	8
5	#4	7'-6"	V4	5	5					5	#4	7'-3"	V6	5	5
2	#6	8'-0"	V5	2	2					240	#5	5'-9"	V7	120	120
2	#4	7'-3"	V6	1	1					22	#5	6'-9"	V8	10	12
2	#4	7'-3"	V7	1	1					5	#4	7'-0"	V9	5	5
2	#6	9'-0"	V10	2	2					SUBSTRUCTURE END BENT 4					
2	#4	10'-6"	V11	1	1					6	#5	5'-0"	A1	6	6
2	#6	9'-9"	V12	2	2					6	#5	7'-6"	A2	6	6
24	#2	19'-9"	W1	12	2										



BRIDGE OVER ROUTE 45  
 STATE ROAD-INTERSTATE ROUTE 29  
 IN KANSAS CITY  
 PROJECT NO. I-29-10 (ARTE. I-29) STA. 8+24.26 ± MEDIAN  
 PLATTE COUNTY

305

No. 90.3  
 June 1961  
 Revised  
 Dec 1964

DETAILED 19" BY 17"  
 CHECKED 19" BY

D, H, V, & R Bars  
 Note: This drawing is not to scale. Follow dimensions.

Sheet No. 2A of 5

FINAL PLANS


A-1159




MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	97	


FINAL PLANS




LONGITUDINAL ELEVATION



TRANSVERSE ELEVATION




LONGITUDINAL ELEVATION




PLAN OF POST AND BASE PLATE

Note: See Standard 86.00 for Details of Blocked Out Post, Rail and Buffer Ends.


DETAILS OF TYPE B GUARD RAIL (BOLT DOWN)



HALF SECTION THRU MEDIAN



PLAN OF MEDIAN SHOWING GUARD RAIL POST SPACING



SECTION A-A

GENERAL NOTES:  
 All other details not shown comply with Std. 86.00  
 Grout Complies with Std. Specs. Sec. 106.1.5  
 Tightening of nuts on bolts connecting rail members and post shall be to the extent that longitudinal movement of the bolt in slotted holes is possible. After tightening in this manner the top of the bolt deformed in such a way as to prevent loss of nut.  
 Guard Rail Posts set normal to grade.  
 Buffer End for Type B Guardrail required at each end of bridges.  
 All bridge guardrail was galvanized

FINISHED

BRIDGE OVER ROUTE 45  
 STATE ROAD - INTERSTATE ROUTE 29  
 CITY  
 I-29-10 (RTE. 1-29) STA. 823+12.26 E MEDIAN  
 COUNTY

PLAT

COUNTY

Sheet No. 3 of 5

FINAL PLANS

A-1159

DETAILED JAN 1966 BY H.S.  
 CHECKED FEB 1966 BY J.E.R.

Note: This drawing is not to scale. Follow dimensions.


307

GENERAL NOTES:

All handrail posts set normal to grade. Aluminum tube handrail bent to conform to vertical and horizontal alignment of parapet. Aluminum washer shims between top of parapet and post base may be used for adjusting handrail alignment. Maximum thickness of shims to be 1/8". Where more tilting of post is required for proper alignment, concrete bearing areas shall be ground down. All parts of handrail, except anchor bolts, nuts, washers, and set screws are to be of aluminum material. The contract unit price per linear foot of "Bridge Rail" shall include furnishing and erecting the handrail complete with anchor bolts, shims and insulating compound. All fillets 1/4" except as noted. All drafts 3° except as noted. Pipe rail to be fabricated in two or three panel lengths unless otherwise approved. Omit set screw on side near filled joint in parapet at all expansion posts. Top of curbs and parapets to be built parallel to grade with curb and parapet joints (except at end posts), normal to grade. Concrete end posts to be vertical. All exposed edges of end posts, parapets and curbs have 1/8" radius. If the contractor desires, he may use drive fit cast aluminum end caps in lieu of welded aluminum closure plates. Integrally cast test coupons and a coat of clear lacquer specified in Std. Spec. 56.2.4 and 56.3.5 respectively will not be required for these rail posts.


MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19 88		




POST DETAILS


SECTION THRU HANDRAIL




SINGLE TUBE ALUMINUM RAILING



FILLED JOINT DETAILS




PLAN OF END POSTS



PLAN OF CURB SHOWING RAIL POST SPACING


SPAN	REINFORCING		
	(1-2)	(2-3)	(3-4)
CURB	#5-C4 (2 Units)	#5-C3 (3 Units)	#5-C6 (2 Units)
PARAPET	#5-R3 (2 Units)	#5-R9 (2 Units)	#5-R10 (2 Units)

Note: For horizontal curb and parapet bars use minimum lap of 15" for #5.




ELEVATION OF END POST

END POST ORDINATES



SECTION B-B

SECTION C-C



Note: Plastic water stop placed in all parapet and curb filled joints, except at end bits. Cost of plastic water stop complete in place to be included in unit price bid for concrete.

BRIDGE OVER ROUTE 45  
STATE ROAD - INTERSTATE ROUTE 29  
IN ANSAS CITY  
PROJECT NO. I-29-10 (RTE. 1-29) STA. 828+24.26 & MEDIAN  
PLATTE COUNTY

308

Revised Oct. 1965  
Nov. 1963

DETAILED JAN. 1965 BY H.H.S.  
CHECKED FEB. 1965 BY J.L.

Note: This drawing is not to scale. Follow dimensions.



Sheet No. 4 of 5

FINAL PLANS

A-1159

MISSOURI HIGHWAY AND TRANSPORTATION COMMISSION

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		89	49	
SEC./SUR. 20129 TWP. 51N RGE. 38W					



GENERAL NOTES:

- Design Specifications: A.A.S.H.T.O. 1977 and Interims thru 1982
- Design Unit Stresses:  
Class B1 Concrete  $f_c = 4000$  psi  
Reinforcing Steel (Grade 60)  $f_y = 60,000$  psi
- Joint Filler:  
All joint filler shall meet the requirement of Std. Spec. 1057.2-4, except as noted.
- Reinforcing Steel:  
Minimum clearance to reinforcing shall be 1 1/2" unless otherwise shown.
- Traffic:  
Traffic over structure to be maintained during construction.
- Construction Clearance:  
A minimum vertical clearance of 14'-9" from crown of existing lanes and a minimum lateral clearance of 22'-0" centered on existing lanes shall be maintained during construction.
- Existing Work:  
Outline of old work is indicated by light dashed lines. Heavy lines indicate new work.  
Bars bonded in old concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available old bars shall extend into new concrete at least 30 diameters for smooth bars and 30 diameters for deformed bars.
- Approach Slab:  
Taper roadway surfacing at bridge ends to match concrete wearing surface. (Edwy. Item)
- Paint:  
Areas to be enclosed in end bent concrete shall be painted one coat of System C primer and scratched or damaged surfaces are to be touched up before concrete is poured.  
System B by contractor in accordance with Std. Spec. 712.13. Color of the final coat for System B shall be aluminum.

ESTIMATED QUANTITIES	
ITEM	TOTAL
Concrete Wearing Surface * ( )	Sq. Yd. 1979
Repairing Concrete Deck (Half-soling)	Sq. Ft. 542
Full Depth Repair	Sq. Ft. 171
Safety Barrier Curb	Lin. Ft. 363
Class B1 Concrete	Cu. Yd. 507
Reinforcing Steel	Lb. 2940
Painting **	Lump Sum 1
Special Work	Lump Sum 1
Reinforcing Steel (Epoxy Coated)	Lb. 2460

\* See Job Special Provisions for alternate use of concrete wearing surface. Alternate "A" = 1 1/2" (min) Latex Modified Concrete. Alternate "B" = 2 1/2" (min) Low Slump Concrete.  
\*\* Approximately 186.0 tons of existing steel are to be painted.

REPAIRS TO BRIDGE OVER RTE. 45

STATE ROAD - INTERSTATE ROUTE 29  
IN KANSAS CITY ST A. 828 +02.28 (S.B.L.)  
PROJECT NO. IR-29-1(80) STA. 828 +46.24 (N.B.L.)  
JOB NO. 4-1029-137C RTE. I-29  
PLATTE COUNTY  
DATE December 17, 1984


STD.
STD-706.35
A-1159 R

DESIGNED Sept. 1984  
DETAILED Sept. 1984  
CHECKED Nov. 1984


Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1 of 1



STATE	PROJ. NO.	SHEET NO.
MO.		50



HALF SECTION - EXISTING



HALF SECTION - PROPOSED



DETAILS OF OPEN SLAB AREAS (STAGE 2)


Note: Open Areas are to remain open during stage 1 removal and construction.

Note: The contractor may use one of the following anchor systems for the barrier curb.

- (1) Molly Parabond Capsule Anchors
- (2) Hilti HVA Adhesive Anchors
- (3) Sup-B Set Synthetic Resin Capsule Anchors

These anchor systems shall be installed according to the manufacturer's specifications except that an epoxy coated 5/8" dia. G. 60 reinforcing bar 8'-6" long shall be substituted for the epoxy coated or galvanized threaded rod stud.

Cost of furnishing and installing the anchor system complete in place shall be included in the price bid per lin. ft. of barrier curb.



DETAILED Sept. 1984  
CHECKED Nov. 1984



Note: This drawing is not to scale. Follow dimensions.

Sheet No. 2 of 9

PLATTE COUNTY

A-1159R

STATE	PROJ. NO.	SHEET NO.
MO.		51



DETAILED Sept. 1954  
 CHECKED Nov. 1954

Note: This drawing is not to scale. Follow dimensions.

PART PLAN OF END BENT  
 DETAILS OF END BENT NO. 1 - N.B.L.


Note: #6H7 bars shall extend 4" (min) beyond construction joint. (See Special Provisions)

Sheet No. 3 of 7


PLATTE COUNTY

A-1159R

STATE	PROJ. NO.	SHEET NO.
MO.		52



PART SECTION NEAR END BENT



PART PLAN OF END BENT

DETAILS OF END BENT NO. 1 - S.B.L.

DETAILED Sept. 1934  
CHECKED Nov. 1934

Note: This drawing is not to scale. Follow dimensions.

Note: #6H7 bars shall extend 4" (min) beyond construction joint. (See special provisions)  
Sheet No. 4 of 9.

PLATTE COUNTY


A-1159R

STATE	PROJ NO	SHEET NO
MO		53


Remove existing median on backwall to about top of the approach haunch.

For details and reinforcement of safety barrier curb see sht. No. 8.

For repairs to existing curb and parapet see sht. No. 1.




PART SECTION NEAR END BENT



Note: For location of Stage Construction see sht. No. 1. For location of Open Areas see sht. No. 2.

78



PART PLAN OF END BENT  
DETAILS OF END BENT NO. 4 - S.B.L.

Note: #6H7 bars shall extend 4" (min.) beyond construction joint. (See special provisions)

DETAILED 12-15-84  
CHECKED Nov. 1984


Note: This drawing is not to scale. Follow dimensions.

Sheet No. 5 of 9

PLATTE COUNTY

A-1159R

STATE	PROJ. NO.	SHEET NO.
MO.		54



DETAILED Sept. 1984  
 CHECKED Nov. 1984

This drawing is not to scale. Follow dimensions.

PART PLAN OF END BENT  
 DETAILS OF END BENT NO. 4 -- N.B.L.










Note: #6H7 bars shall extend 4" (min.) beyond construction joint. (see special provisions)

Sheet No. 6 of 9

PLATTE COUNTY

A-1159R

STATE	PROJ. NO.	SHEET NO.
MO.		55



80


Remove existing median on back wall to a line about top of approach haunch. Tie vertical steel to existing vertical steel.

DETAILED Sept. 19 54  
CHECKED Nov. 19 54


Note: Cost of concrete and reinforcement required for Median Closure Wall, complete in place shall be included in unit prices bid per linear foot of Safety Barrier Curb.  
Note: This drawing is not to scale. Follow dimensions.

Note: Existing rail posts complete with anchor bolts and insulating material (Std. Spec. 712.1.5) are to be re-installed at original location. Set screws are to be omitted on re-installed Rail Posts.

STATE	PROJ. NO.	SHEET NO.
MO.		56




SECTION NEAR RIGHT BARRIER CURB - N.B.L.




SECTION NEAR LEFT BARRIER CURB - S.B.L.

Note: Top of barrier curb to be built parallel to grade with barrier curb joints (except at end bents) normal to grade. All exposed edges of barrier curb shall have 1/2" radius or 3/8" bevel unless otherwise noted. When the barrier curb is bid by linear feet, the contract unit price shall include the cost of all concrete and reinforcement, complete in place. Concrete in the safety barrier curb shall be 7. Measurement of safety barrier curb is 100% nearest linear foot for each structure, measured along the outside top of slab from full face of end bent to full face of end bent. Longitudinal dimensions shown are parallel to grade at top of slab. Longitudinal dimensions are based on original plans.



ANCHOR BAR DETAIL

Note: Each anchor bar (A.S.T.M. A-36) shall be furnished with a 1/2" 13" x 13" PL (A.S.T.M. A-36) and one heavy hex nut (A.S.T.M. A-307). This entire assembly shall be galvanized in accordance with A.S.T.M. A-123 and A-133. After the concrete in the barrier curb has set, the plate and nut shall be installed and the nut tightened snug tight and the threads burred. Cost of furnishing and installing anchor bar assemblies shall be included in the price bid per lin. ft. of barrier curb. For optional Anchoring System see Sht. # 2.



PART SECTION NEAR LEFT BARRIER CURB

SECTION A-A

Note: Use a minimum lap of 17" for #5 horizontal barrier bars.

DETAILED Sept. 19 84  
CHECKED Nov. 19 84

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 8 of 9

PLATTE COUNTY


A-1159R

**COMPLETE BILL OF REINFORCING STEEL**

NO. REQD.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	DIMENSIONS										NOMINAL LENGTH FT.	ACTUAL LENGTH FT.	WEIGHT LBS.
								B	C	D	E	F	H	K	FT.	IN.	FT.			
BENT 1 NGL																				
15	6H1	DIAPHRAGM		20				10	6.000							10	6.10	6	237	
3	6H2	DIAPHRAGM		20				2	9.000							2	9	2	12	
3	6H3	DIAPHRAGM		20				3	8.000							3	8	3	17	
1	6H4	DIAPHRAGM		20				33	0.000							33	0	33	50	
1	6H5	DIAPHRAGM		20				29	9.000							29	9	29	45	
4	6H6	DIAPHRAGM	E	20				31	6.000						31	6	31	159		
6	6H7	DIAPHRAGM	E	20				29	11.000						29	11	29	270		
57	4U1	DIAPHRAGM		19				2	7.500	2	1.500				4	9	4	178		
59	4U2	DIAPHRAGM	E	19				2	7.500	3	4.000				6	0	5	225		
118	6V1	DIAPHRAGM		20				18	18.000						18	18		266		
BENT 1 SBL																				
15	6H1	DIAPHRAGM		20				10	6.000						10	6	10	237		
3	6H2	DIAPHRAGM		20				2	9.000						2	9	2	12		
3	6H3	DIAPHRAGM		20				3	8.000						3	8	3	17		
1	6H4	DIAPHRAGM		20				33	0.000						33	0	33	50		
1	6H5	DIAPHRAGM		20				29	9.000						29	9	29	45		
4	6H6	DIAPHRAGM	E	20				31	6.000						31	6	31	159		
4	6H7	DIAPHRAGM	E	20				29	11.000						29	11	29	150		
57	4U1	DIAPHRAGM		19				2	7.500	2	1.500				4	9	4	178		
57	4U2	DIAPHRAGM	E	19				2	7.500	3	4.000				6	0	5	222		
118	6V1	DIAPHRAGM		20				18	18.000						18	18		266		
BENT 4 NBL																				
15	6H1	DIAPHRAGM		20				10	6.000						10	6	10	237		
3	6H2	DIAPHRAGM		20				2	9.000						2	9	2	12		
3	6H3	DIAPHRAGM		20				3	8.000						3	8	3	17		
1	6H4	DIAPHRAGM		20				33	0.000						33	0	33	50		
1	6H5	DIAPHRAGM		20				29	9.000						29	9	29	45		
4	6H6	DIAPHRAGM	E	20				31	6.000						31	6	31	159		
4	6H7	DIAPHRAGM	E	20				29	11.000						29	11	29	150		
57	4U1	DIAPHRAGM		19				2	7.500	2	1.500				4	9	4	178		
57	4U2	DIAPHRAGM	E	19				2	7.500	3	4.000				6	0	5	222		
57	6V1	DIAPHRAGM		20				18	18.000						18	18		128		
BENT 4 SBL																				
15	6H1	DIAPHRAGM		20				10	6.000						10	6	10	237		
3	6H2	DIAPHRAGM		20				2	9.000						2	9	2	12		
3	6H3	DIAPHRAGM		20				3	8.000						3	8	3	17		
1	6H4	DIAPHRAGM		20				33	0.000						33	0	33	50		
1	6H5	DIAPHRAGM		20				29	9.000						29	9	29	45		
4	6H6	DIAPHRAGM	E	20				31	6.000						31	6	31	159		
4	6H7	DIAPHRAGM	E	20				29	11.000						29	11	29	150		
57	4U1	DIAPHRAGM		19				2	7.500	2	1.500				4	9	4	178		
57	4U2	DIAPHRAGM	E	19				2	7.500	3	4.000				6	0	5	222		
57	6V1	DIAPHRAGM		20				18	18.000						18	18		128		


**COMPLETE BILL OF REINFORCING STEEL**

NO. REQD.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	DIMENSIONS										NOMINAL LENGTH FT.	ACTUAL LENGTH FT.	WEIGHT LBS.
								B	C	D	E	F	H	K	FT.	IN.	FT.			
CURB AND PARAPET																				
22	5C1	CURB AND PARAPET		E 19	S			2	0.000							2	7	2	57	
22	5C2	CURB AND PARAPET		E 12	S			2	0.000							2	0	0	7	
5	5C3	CURB AND PARAPET		E 19	S			2	11.000							2	11	0	71	
18	5C4	CURB AND PARAPET		E 11	S			2	11.000							2	11	0	29	
12	5C5	CURB AND PARAPET		E 20				3	0.000							3	0	0	92	
12	5C6	CURB AND PARAPET		E 20				4	2.000							4	2	2	40	
8	5C7	CURB AND PARAPET		E 12	S			2	11.000							2	11	0	52	
BARRIER CURB																				
386	5R1	BARRIER CURB		E 15				2	7.125						2	7	0	1107		
386	5R2	BARRIER CURB		E 19				2	7.000						2	7	0	1107		
7	5R3	BARRIER CURB		E 20				40	6.000						40	6	0	296		
14	5R4	BARRIER CURB		E 20				9	9.000						9	9	0	580		
7	5R5	BARRIER CURB		E 20				56	9.000						56	9	0	829		
7	5R6	BARRIER CURB		E 20				35	5.000						35	5	0	259		
7	5R7	BARRIER CURB		E 20				39	7.000						39	7	0	289		
7	5R8	BARRIER CURB		E 20				36	4.000						36	4	0	265		
16	5R10	BARRIER CURB		E 13	S			6.000	2	0.000					6	0	0	93		
12	5R11	BARRIER CURB		E 27	S			12.000		9.000					11	125	6.000	98		
12	5R12	BARRIER CURB		E 11	S			12.000		18.000					3	2	3	35		
4	5R13	BARRIER CURB		E 20				20.000							20	0	0	7		
24	5R14	BARRIER CURB		E 20				3	5.000						3	5	0	86		
10	5R15	BARRIER CURB		E 20				3	9.000						3	9	0	39		
2	5R16	BARRIER CURB		E 20				3	11.000						3	11	0	8		
12	5R17	BARRIER CURB		E 20				4	2.000						4	2	0	52		
16	5H50	CLOSURE WALL		E 20				4	10.000						4	10	0	81		
16	5H51	CLOSURE WALL		E 15				7.250		4	3.000				4	0	0	81		
8	5H52	CLOSURE WALL		E 20				2.000							4	2	0	35		
40	5V50	CLOSURE WALL		E 20				3	10.000						3	10	0	160		
END OF BAR LIST																				



82

STD. 90.8  
MAY 1974  
REVISED  
MAY 1984




**STIRRUP HOOK DIMENSIONS**

GRADES 40-50-60 KSI

BAR SIZE	D (IN.)	90° HOOK		135° HOOK		APPROX. H
		HOOK A OR G				
#3	1-1/2"	4"	4"	4"	4"	2-1/2"
#4	2"	4-1/2"	4-1/2"	4-1/2"	4-1/2"	3"
#5	2-1/2"	6"	6"	5-1/2"	5-1/2"	3-3/4"
#6	4-1/2"	8"	8"	7"	7"	4-1/2"

NOTE: UNLESS OTHERWISE NOTED DIAMETER "D" IS THE SAME FOR ALL BENDS AND HOOKS ON A BAR.  
Note: This drawing is not to scale. Follow dimensions.



**END HOOK DIMENSIONS**

BAR SIZE	180° HOOKS		90° HOOKS	
	GRADE 40	GRADE 60	ALL GRADES	ALL GRADES
#3	5"	2-3/4"	5"	3"
#4	6"	3-1/2"	6"	4"
#5	7"	4-1/2"	7"	5"
#6	8"	5-1/4"	8"	6"
#7	9"	6-1/4"	10"	7"
#8	10"	7"	11"	8"
#9	12"	8"	15"	11-1/4"
#10	13"	9"	17"	12-3/4"
#11	14"	10"	19"	14-1/4"
#14	21-2"	20-1/2"	21-2"	20-1/2"

Sheet No. 9 of 9

**NOTES:**

ALL STANDARD HOOKS AND BENDS OTHER THAN 180 DEG. TO BE BENT WITH SAME PROCEDURE AS FOR 90 DEG. STD. HOOKS

HOOKS AND BENDS SHALL BE IN ACCORDANCE WITH THE PROCEDURES AS SHOWN ON THIS SHEET.

E - EPOXY COATED REINFORCEMENT.

S - STIRRUP.

X - BAR IS INCLUDED IN SUBSTRUCTURE QUANTITIES.

V - BAR DIMENSIONS VARY IN EQUAL INCREMENTS BETWEEN DIMENSIONS SHOWN ON THIS LINE AND THE FOLLOWING LINE.

NO. EA. - NUMBER OF BARS OF EACH LENGTH.

NOMINAL LENGTHS - ARE BASED ON OUT TO OUT DIMENSIONS SHOWN IN BENDING DIAGRAMS AND ARE LISTED FOR FABRICATORS USE. (NEAREST INCH)

ACTUAL LENGTHS - ARE MEASURED ALONG CENTERLINE BAR TO THE NEAREST INCH.



PAYMENTS ARE BASED ON ACTUAL LENGTHS.

PLATTE COUNTY A-1159R

MISSOURI HIGHWAY AND TRANSPORTATION COMMISSION

FINAL PLANS

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19	49	
SEC. 15, R. 20, T29 TWP. 5 N. RGE. 33W					



GENERAL NOTES:

- Design Specifications: A.A.S.H.T.O. 1977 and Interims thru 1982
- Design Unit Stresses:
  - Class B1 Concrete  $f'_c = 4,000$  psi
  - Reinforcing Steel (Grade 60)  $f_y = 60,000$  psi
- Joint Filler: All joint filler shall meet the requirement of Std. Spec. 1057.2.4. except as noted.
- Reinforcing steel: Minimum clearance to reinforcing shall be  $1\frac{1}{2}$ " unless otherwise shown.
- Traffic: Traffic over structure to be maintained during construction.
- Construction Clearances:
  - A minimum vertical clearance of 14'-9" from crown of existing lanes and a minimum lateral clearance of 23'-0" centered on existing lanes shall be maintained during construction.
- Existing Work: Outline of old work is indicated by light dashed lines. Heavy lines indicate new work.
- Bars bonded in old concrete not removed shall be clearly stripped and embedded into new concrete where possible. If length is available, old bars shall extend into new concrete at least 40 diameters for smooth bars and 30 diameters for deformed bars.
- Approach Slab: Taper roadway surfacing at bridge ends to match concrete wearing surface. (Edwy. Item)
- Paint: Areas to be encased in end bent concrete shall be painted one coat of System C primer and scratched or damaged surfaces are to be touched up before concrete is poured.
- System B by contractor in accordance with Std. Spec. 712.13. Color of the final coat for System B shall be aluminum.

FINAL QUANTITIES		
ITEM		TOTAL
Concrete Wearing Surface * Alt. B	Sq. Yd.	1979
Repairing Concrete Deck (Half-soling)	Sq. Ft.	3139
Full Depth Repair	Sq. Ft.	764
Safety Barrier Curbs	Lin. Ft.	363
Class B1 Concrete	Cu. Yd.	507
Reinforcing Steel	Lb.	2940
Painting **	Lump Sum	1.00
Special Work	Lump Sum	1.00
Reinforcing Steel (Epoxy Coated)	Lb.	2460

\* See Job Special Provisions for alternate use of concrete wearing surface. Alternate "B" is low slump concrete. Alternate "B" = 22" (min) Low Slump Concrete.

\*\* Approximately 36.0 tons of existing steel are to be painted.

B.M.

REPAIRS TO BRIDGE OVER RTE. 45

STATE ROAD - INTERSTATE ROUTE 29

IN KANSAS CITY STA. 828 +02.28 ± (S.B.L.)  
 PROJECT NO. IR-29-1(80) STA. 828 +46.24 ± (N.B.L.)

JOE NO. 4-I029-137C RTE. I-29  
 PLATTE COUNTY

STD.
STD. 706.35
A 11595


DATE December 17, 1984

DESIGNED Sept. 1984  
 DETAILED Sept. 1984  
 CHECKED Nov. 1984

Note: This drawing is not to scale. Follow dimensions.


Sheet No. 1A of 9.

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.		19		




PARTIAL ELEVATION  
OVER E. BOUND RTE. 45 SHOWN  
W. BOUND SIMILAR EXCEPT OPPOSITE GRADE

SIGN  
10'-6" x 6'-0"




SECTION A-A

NOTE: ALL ANGLES SHALL BE 4x4x3/8




PARTIAL PLAN

NOTE: DRILL 1/16" Φ HOLES FOR 3/8" Φ H.S. BOLTS IN VERTICAL ANGLES FOR ATTACHING SIGN TO BRACKETS. SEE STD. DWGS 903.03 FOR Z-BAR LOCATIONS ON SIGN.



DETAIL "A"

SEE ELEVATION FOR DIRECTION OF L<sub>E</sub>



LOCATION SKETCH

GENERAL NOTES

STRUCTURAL STEEL SHALL BE A.S.T.M. A36, GALVANIZED FIELD CONNECTIONS HIGH STRENGTH BOLTS 3/8" Φ, HOLES 1/16" Φ EXCEPT AS NOTED. ALL BOLTS, NUTS AND WASHERS SHALL BE GALVANIZED. THE TURN-OF-NUT METHOD OF OBTAINING BOLT TENSION FOR HIGH STRENGTH BOLTS MAY BE USED (SEE STD. SPEC. 712.11.2)  
CONCRETE ANCHORS SHALL BE THE NON-DRILLING EXPANSION TYPE. THEY SHALL HAVE A CERTIFIED CONCRETE PULL-OUT STRENGTH (ULTIMATE LOAD) OF AT LEAST 15,500 POUNDS IN 3500 PSI CONCRETE. THE HOLE SHALL BE PRE-DRILLED WITH A CONVENTIONAL CARBIDE MASONRY BIT.  
THE COST OF FURNISHING AND ERECTING THE SIGN SUPPORTS, INCLUDING THE CONCRETE ANCHORS COMPLETE IN PLACE, SHALL BE PAID FOR AS FABRICATED SIGN SUPPORT BRACKETS, LUMP SUM.  
CENTER AND LEVEL SIGN ON BRACKETS.  
SIGNS TO BE FURNISHED BY OTHERS.

BRIDGE: SIGN SUPPORT BRACKETS

STATE ROAD: INTERSTATE RTE. I-29 & RTE. 45  
JOB NO. J--4 I-29-464

DETAILED JULY 1983  
CHECKED AUG. 1983

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 1 of 1.


STATE OF MISSOURI  
LITTLE ROCK COUNTY

A-1159A

230

MISSOURI HIGHWAY AND TRANSPORTATION COMMISSION

STATE	PROJ. NO.	SHEET NO.
MO.		137
SEC./SUR. 20 & 29 TWP. 51N RGE. 33W		



PLAN OF CURB BLOCKOUT SHOWING REINFORCEMENT (NORTHBOUND ROADWAY)

GENERAL NOTES:

DESIGN SPECIFICATIONS:

A.A.S.H.T.O.-1996

DESIGN UNIT STRESSES:

Class B1 Concrete (Curb Blockout & End Bent Wing) f'c=4000 psi  
Reinforcing Steel (Grade 60) fy=60,000 psi

JOINT FILLER:

All joint filler shall meet the requirements of Std. Spec. 1057.2-3, except as noted.

REINFORCING STEEL:

Minimum clearance to reinforcing steel shall be 1 1/2" unless otherwise shown.

OLD WORK:

Outline of old work is indicated by light dashed lines. Heavy lines indicate new work.

VERIFY DIMENSIONS:

Contractor shall verify dimensions in field before ordering new material.

NOTES:

Bars bonded in old concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available, old bars shall extend into new concrete at least 40 diameters for smooth bars and 30 diameters for deformed bars, unless otherwise noted.

The contractor shall use one of the resin anchor systems listed in the job special provisions for the curb blockout. These anchor systems shall be installed according to the manufacturer's specifications, except as modified by the job special provisions and that an epoxy coated #5 grade 60 reinforcing bar as shown shall be substituted for the 5/8" threaded rod stud.

Cost of furnishing and installing the anchor systems complete in place shall be included in the price bid per linear foot of curb blockout.

The 5/8" diameter resin anchor systems shall have a minimum ultimate pullout strength of 18,600 lbs. in concrete with f'c= 4000 psi. See special provisions.

NOTES FOR CURB BLOCKOUT

Concrete in curb blockout shall be Class B1. Measurement of curb blockout is to the nearest linear foot measured at the gutter line from end of wing to end of wing.

All exposed edges of curb blockout shall have 1/2" radius or 3/8" bevel unless otherwise shown.

Payment for concrete and reinforcing steel in curb blockout complete in place shall be included in the contract unit price for the curb blockout per linear foot.

Cost of any concrete end post and curb removal shall be considered completely covered in the contract unit price for the curb blockout per linear foot.

Minimum lap for R-bar reinforcement to be 2'-11".

TRAFFIC HANDLING:

See roadway plans for traffic control during construction.

EXISTING PARAPET RAILING:

Where parapet is removed reattach parapet railing to new concrete using 3/4"x10" anchor bolts. Leave set screws out of rail post for expansion. Cost to be included in unit price for curb blockout.

EXISTING LOW SLUMP CONCRETE OVERLAY:

Any damage to the existing low slump concrete overlay shall be repaired or replaced as directed by the engineer. No direct payment will be made for any replacement or repairs to the low slump concrete overlay.

EXISTING SLOPE PROTECTION:

Contractor shall be responsible for any damage to existing paved slope protection.

REPAIRS TO: BRIDGE OVER ROUTE 45

STATE ROAD FROM RTE. 1-635 TO RTE. 152

ABOUT 2 MILES NW OF RTE. 1-635

PROJECT NO.

STA. 828+46.24 (MATCH

JOB NO. J411246


RTE. 1-29 (NBL) EXISTING)

PLATTE


COUNTY

DATE 1/27/97


A11592



TYPICAL SECTION THRU CURB BLOCKOUT



FILLED JOINT DETAIL



DETAIL OF TEMPORARY TRAFFIC BARRIER

ESTIMATED QUANTITIES

ITEM	TOTAL
Curb Blockout Lin.Ft.	199
*Rehabilitation of Existing Wing Lump Sum	1

\* Cost of partial removal of wing, resin anchors, excavation, Class B1 Concrete and reinforcing steel for northeast wing at Bent #1 to be included in bid price for rehabilitation of existing wing. (See Special Provisions)

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.




DATE 1/15/97

SHEET NO. 1 OF 6

DESIGNED MAY 1997  
DETAILED MAY 1997  
CHECKED DEC. 1997


326

STATE	PROJ. NO.	SHEET NO.
MO.		138




PLAN OF CURB BLOCKOUT SHOWING RESIN ANCHOR SPACING (NORTHBOUND ROADWAY)

Note: Curb Blockout Joint Filler shall match those of Existing Structure.




RESIN ANCHOR SYSTEMS DETAILS



TYPICAL SECTION THRU CURB

\* Shift Resin Anchors to clear existing steel anchor bolts for tube rail.



PART SECTION A-A


227


DETAILED MAY 1997  
CHECKED DEC. 1997

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.


SHEET NO. 2 OF 6.

PLATTE COUNTY






PLAN SHOWING END POST REINFORCEMENT




SECTION A-A




PLAN SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS


STATE	PROJ. NO.	SHEET NO.
MO.		139




SECTION C-C




ELEVATION SHOWING END POST REINFORCEMENT




SECTION B-B



ELEVATION SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS




SECTION D-D




ELEVATION OF EXISTING END POST, CURB, PARAPET AND PARTIAL REMOVAL OF BRIDGE DECK SHOWING CONCRETE REMOVAL


Note: For limits of removal of wing see sheet No. 5.




SECTION F-F



RUSTICATION DETAIL



DETAILS OF GUARD RAIL ATTACHMENT




DETAIL "E"




228

DETAILED NOV. 1997  
CHECKED DEC. 1997


STATE	PROJ. NO.	SHEET NO.
MO.		140




PLAN SHOWING END POST REINFORCEMENT




SECTION A-A




PLAN SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS




SECTION C-C




ELEVATION SHOWING END POST REINFORCEMENT




SECTION B-B




ELEVATION SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS




SECTION D-D



ELEVATION OF EXISTING END POST SHOWING CONCRETE REMOVAL



DETAILS OF GUARD RAIL ATTACHMENT



DETAIL "E"

DETAILS OF END POST ON SOUTHEAST WING

622  
CHECKED NOV. 1997  
DEC. 1997

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.

SHEET NO. 4 OF 6.


PLATTE COUNTY




A11592

Note: For location of wing see sheet No. 1. 13'-4 1/2" ±


State	Proj. No.	Sheet No.
MO		141




ELEVATION SHOWING WING REINFORCEMENT & DIMENSIONS




SECTION B-B




SECTION C-C




ELEVATION SHOWING WING RESIN ANCHOR SYSTEMS & DIMENSIONS




PLAN SHOWING WING REINFORCEMENT & DIMENSIONS



PLAN A-A



ELEVATION OF EXISTING WING SHOWING CONCRETE REMOVAL



PLAN SHOWING WING RESIN ANCHOR SYSTEMS & DIMENSIONS

230

DETAILS SHOWING REHABILITATION OF NORTHEAST WING AT BENT #1

DETAILED DEC. 1997  
CHECKED DEC. 1997





BILL OF REINFORCING STEEL


BILL OF REINFORCING STEEL

Table with columns: NO. REQ'D., MARK NO., LOCATION, EPOXY (E), SHAPE NO., STIRRUP (S), SUBSTR. (X), VARIES (V), NO. EACH, DIMENSIONS (B, C, D, E, F, H, K), NOMINAL LENGTH, ACTUAL LENGTH, WEIGHT.

Table with columns: NO. REQ'D., MARK NO., LOCATION, EPOXY (E), SHAPE NO., STIRRUP (S), SUBSTR. (X), VARIES (V), NO. EACH, DIMENSIONS (B, C, D, E, F, H, K), NOMINAL LENGTH, ACTUAL LENGTH, WEIGHT.




STIRRUP HOOK DIMENSIONS table with columns: BAR SIZE, D (IN.), 90° HOOK, 135° HOOK, APPROX. H.



END HOOK DIMENSIONS table with columns: BAR SIZE, D (IN.), ALL GRADES, 180° HOOKS, 90° HOOKS.

NOTE: ALL STANDARD HOOKS AND BENDS OTHER THAN 180 DEG. TO BE BENT WITH THE SAME PROCEDURE AS FOR 90 DEG. STD. HOOKS. HOOKS AND BENDS SHALL BE IN ACCORDANCE WITH THE PROCEDURES AS SHOWN ON THIS SHEET.




STD 90.6 REVISED MAY 1974 OCT. 1997

90° STIRRUP 135° STIRRUP CHECKED DEC. 1997

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.

MISSOURI HIGHWAY AND TRANSPORTATION COMMISSION

STATE	PROJ. NO.	SHEET NO.
		143
SEC. / SUR. 20 & 29 TWP. 51N RGE. 33W		



PLAN OF CURB BLOCKOUT SHOWING REINFORCEMENT (SOUTHBOUND ROADWAY)

GENERAL NOTES:

**DESIGN SPECIFICATIONS:**  
A.A.S.H.T.O.-1996

**DESIGN UNIT STRESSES:**  
Class B1 Concrete (Curb Blockout & End Bent Wing)  $f'_c=4000$  psi  
Reinforcing Steel (Grade 60)  $f_y=60,000$  psi

**JOINT FILLER:**  
All joint filler shall meet the requirements of Std. Spec. 1057.2.4, except as noted.

**REINFORCING STEEL:**  
Minimum clearance to reinforcing steel shall be  $\frac{1}{2}$ " unless otherwise shown.

**OLD WORK:**  
Outline of old work is indicated by light dashed lines. Heavy lines indicate new work.

**VERIFY DIMENSIONS:**  
Contractor shall verify dimensions in field before ordering new material.

**NOTES:**  
Bars bonded in old concrete not removed shall be cleanly stripped and embedded into new concrete where possible. If length is available, old bars shall extend into new concrete at least 40 diameters for smooth bars and 30 diameters for deformed bars, unless otherwise noted.

The contractor shall use one of the resin anchor systems listed in the job special provisions for the curb blockout. These anchor systems shall be installed according to the manufacturer's specifications, except as modified by the job special provisions and that an epoxy coated #5 grade 60 reinforcing bar as shown shall be substituted for the  $\frac{5}{8}$ " threaded rod stud.

Cost of furnishing and installing the anchor systems complete in place shall be included in the price bid per linear foot of curb blockout.

The  $\frac{5}{8}$ " diameter resin anchor systems shall have a minimum ultimate pullout strength of 18,600 lbs. in concrete with  $f'_c=4000$  psi. See special provisions.

NOTES FOR CURB BLOCKOUT


Concrete in curb blockout shall be Class B1. Measurement of curb blockout is to the nearest linear foot measured at the gutter line from end of wing to end of wing.

All exposed edges of curb blockout shall have  $\frac{1}{2}$ " radius or  $\frac{3}{8}$ " bevel unless otherwise shown.


Payment for concrete and reinforcing steel in curb blockout complete in place shall be included in the contract unit price for the curb blockout per linear foot.

Cost of any concrete end post and curb removal shall be considered completely covered in the contract unit price for the curb blockout per linear foot.


Minimum lap for R-bar reinforcement to be 2'-11".



TYPICAL SECTION THRU CURB BLOCKOUT



FILLED JOINT DETAIL



DETAIL OF TEMPORARY TRAFFIC BARRIER

TRAFFIC HANDLING:

See roadway plans for traffic control during construction.

EXISTING PARAPET RAILING:

Where parapet is removed reattach parapet railing to new concrete using  $\frac{3}{4}$ "x10" anchor bolts. Leave set screws out of rail post for expansion. Cost to be included in unit price for curb blockout.

EXISTING LOW SLUMP CONCRETE OVERLAY:

Any damage to the existing low slump concrete overlay shall be repaired or replaced as directed by the engineer. No direct payment will be made for any replacement or repairs to the low slump concrete overlay.

EXISTING SLOPE PROTECTION:

Contractor shall be responsible for any damage to existing paved slope protection.

ESTIMATED QUANTITIES		
ITEM	UNIT	TOTAL
Curb Blockout	Lin. Ft.	199
*Rehabilitation of Existing Wing	Lump Sum	1

\* Cost of partial removal of wing, resin anchors, excavation, Class B1 Concrete and reinforcing steel for southwest wing at Bent #4 to be included in bid price for rehabilitation of existing wing. (See Special Provisions)



REPAIRS TO: BRIDGE OVER ROUTE 45

STATE ROAD FROM RTE. 1-635 TO RTE. 152

ABOUT 2 MILES NW OF RTE. 1-635

PROJECT NO.

STA. 828+02.28 (MATCH EXISTING)

JOB NO. J411246

RTE. 1-29 (SBL)

PLATTE

COUNTY

DATE 1/27/98


STD.  
A11593

DESIGNED MAY 1997  
DETAILED MAY 1997  
CHECKED DEC 1997

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.


SHEET NO. 1 OF 6

STATE	PROJ. NO.	SHEET NO.
MO.		144




PLAN OF CURB BLOCKOUT SHOWING RESIN ANCHOR SPACING (SOUTHBOUND ROADWAY)

Note: Curb Blockout Joint Filler shall match those of Existing Structure.



RESIN ANCHOR SYSTEMS DETAILS



PART SECTION A-A

\* Shift Resin Anchors to clear existing steel anchor bolts for tube rail.

NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.

DETAILED: WAY 1997  
CHECKED: DFD 1997

SHEET NO. 2 OF 6












PLATTE COUNTY



DATE 1/15/98

A11593

STATE	PROJ. NO.	SHEET NO.
MO.		145



DETAILS OF END POST ON NORTHWEST WING



DATE 11/2/92

DETAILED NOV. 1997  
CHECKED DEC. 1997


NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS.

SHEET NO. 3 OF 6.


PLATTE COUNTY

A11593


STATE	PROJ. NO.	SHEET NO.
MO.		146




PLAN SHOWING END POST REINFORCEMENT




SECTION A-A




PLAN SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS




SECTION C-C




ELEVATION SHOWING END POST REINFORCEMENT




SECTION B-B



ELEVATION SHOWING END POST RESIN ANCHOR SYSTEMS & DIMENSIONS




SECTION D-D




ELEVATION OF EXISTING END POST, CURB, PARAPET AND PARTIAL REMOVAL OF BRIDGE DECK SHOWING CONCRETE REMOVAL


Note: For limits of removal of wing see sheet No. 5.




SECTION F-F



RUSTICATION DETAIL



DETAILS OF GUARD RAIL ATTACHMENT



DATE 1/15/93

DETAILED NOV. 1997  
CHECKED DEC. 1997


NOTE: THIS DRAWING IS NOT TO SCALE. FOLLOW DIMENSIONS

SHEET NO. 4 OF 6.



PLATTE COUNTY

A11593


Note: For location of wing see sheet No. 1. 13'-4 1/2" ±




ELEVATION SHOWING WING REINFORCEMENT & DIMENSIONS




ELEVATION SHOWING WING RESIN ANCHOR SYSTEMS & DIMENSIONS




PLAN SHOWING WING REINFORCEMENT & DIMENSIONS



PLAN A-A



ELEVATION OF EXISTING WING SHOWING CONCRETE REMOVAL



PLAN SHOWING WING RESIN ANCHOR SYSTEMS & DIMENSIONS

DETAILS SHOWING REHABILITATION OF SOUTHWEST WING AT BENT #4





DATE 11/19/93


Drawn by: JLD  
Checked by: JLD  
Date: DEC. 1997

NO. REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS												NOMINAL LENGTH	ACTUAL LENGTH	WEIGHT							
									B		C		D		E		F		H					K						
									FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.				FT.	IN.	FT.	IN.	LBS.		
4	5 R1	BLOCKOUT	E	20					9	7	000							9	7	9	7	40								
22	5 R2	BLOCKOUT	E	20					9	8	000							9	9	9	9	224								
5	5 R3	BLOCKOUT	E	20					10	4	000							10	4	10	4	54								
14	5 R4	BLOCKOUT	E	10	S						11.250	2	7.000					4	6	4	3	63								
2	5 R5	BLOCKOUT	E	10	S						11.250	2	5.000					4	4	4	1	9								
24	5 R6	BLOCKOUT	E	10	S						15.000	2	7.000					5	1	4	1	123								
6	5 R7	BLOCKOUT	E	20					22	8	000							22	8	22	8	139								
12	5 R8	BLOCKOUT	E	20					16	8	000							16	8	16	8	103								
6	5 R9	BLOCKOUT	E	20					30	10	000							30	10	30	10	163								
3	5 R10	BLOCKOUT	E	20					36	4	000							36	4	36	4	74								
2	5 R11	BLOCKOUT	E	20					13	1	000							13	1	13	1	27								
4	5 R12	BLOCKOUT	E	6	S				15	000	2	7.000	9	000				4	7	4	5	18								
4	5 R13	BLOCKOUT	E	10	S				15	000	2	0.000						4	6	4	4	18								
14	5 R14	BLOCKOUT	E	10	S				11.250	22	000							3	9	3	6	51								
2	5 R15	BLOCKOUT	E	10	S				11.250	20	000							3	7	3	4	7								
24	5 R16	BLOCKOUT	E	10	S				15.000	22	000							4	4	4	2	104								
3	5 R17	BLOCKOUT	E	20					9	8	000							9	5	9	5	23								
1	6 H1	S.W. WING	E	20					13	1	000							13	1	13	1	20								
6	6 H2	S.W. WING	E	20					9	8	000							9	9	9	9	65								
1	6 H3	S.W. WING	E	20					12	6	000							12	6	12	6	19								
8	6 H4	S.W. WING	E	20					4	2	000							4	2	4	2	50								
3	6 H5	S.W. WING	E	20			V	1	6	3	000							6	3	6	3	35								
		INCREMENT =							9	3	000							9	3	9	3	35								
		16.375 INCH																												
3	6 H6	S.W. WING	E	20			V	1	9	0	000							9	0	9	0	47								
		INCREMENT =							12	0	000							12	0	12	0	47								
		16.375 INCH																												
2	6 T1	S.W. WING	E	25	S				2	0	750	5	4	750	4	0	000			2	5	125	4	9	875	12	4	12	3	37
14	6 V1	S.W. WING	E	20					1	8	000							4	2	4	3	55								
10	6 V2	S.W. WING	E	20			V	2	2	4	000							2	4	2	4	50								
		INCREMENT =							4	4	000							4	4	4	4	50								
		6.500 INCH																												

NO. REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS												NOMINAL LENGTH	ACTUAL LENGTH	WEIGHT						
									B		C		D		E		F		H					K					
									FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.				FT.	IN.	FT.	IN.	LBS.	




STIRRUP HOOK DIMENSIONS				
GRADES 40 - 50 - 60 KSI				
BAR SIZE	D (IN.)	90° HOOK A OR G	135° HOOK A OR G	APPROX. H
#4	2"	4-1/2"	4-1/2"	3"
#5	2-1/2"	6"	5-1/2"	3-3/4"
#6	4-1/2"	12"	8"	4-1/2"



BAR SIZE	D (IN.)	ALL GRADES			
		180° HOOKS A OR C	180° HOOKS J	90° HOOKS A OR G	90° HOOKS H
#3	2-1/4"	5"	3"	6"	6"
#4	3"	6"	4"	8"	8"
#5	3-3/4"	7"	5"	10"	10"
#6	4-1/2"	8"	6"	12"	12"
#7	5-1/4"	10"	7"	14"	14"
#8	6"	11"	8"	16"	16"
#9	9-1/2"	15"	11-3/4"	19"	19"
#10	10-3/4"	17"	13-1/4"	22"	22"
#11	12"	19"	14-3/4"	21-0"	21-0"
#14	18-1/4"	21-3/4"	21-3/4"	21-7"	21-7"

TWO ADDITIONAL #5-R2 & #6-H2 ARE INCLUDED IN THE BAR BILL FOR TESTING.

NOTE:  
ALL STANDARD HOOKS AND BENDS OTHER THAN 180 DEG. TO BE BENT WITH THE SAME PROCEDURE AS FOR 90 DEG. STD. HOOKS.  
HOOKS AND BENDS SHALL BE IN ACCORDANCE WITH THE PROCEDURES AS SHOWN ON THIS SHEET.  
E = EPOXY COATED REINFORCEMENT.  
S = STIRRUP  
N = BAR IS INCLUDED IN SUBSTRUCTURE QUANTITIES.  
V = BAR DIMENSIONS VARY IN EQUAL INCREMENTS BETWEEN DIMENSIONS SHOWN ON THIS LINE AND THE FOLLOWING LINE.  
NO. EA. = NUMBER OF BARS OF EACH LENGTH.  
NOMINAL LENGTHS ARE BASED ON OUT TO OUT DIMENSIONS SHOWN IN BENDING DIAGRAMS AND ARE LISTED FOR FABRICATORS USE. (NEAREST INCH)  
ACTUAL LENGTHS ARE MEASURED ALONG CENTERLINE BAR TO THE NEAREST INCH.  
PAYWEIGHTS ARE BASED ON ACTUAL LENGTHS.  
FOUR ANGLE OR CHANNEL SPACERS ARE REQUIRED FOR EACH COLUMN SPIRAL. SPACERS ARE TO BE PLACED ON INSIDE OF SPIRALS. LENGTH AND WEIGHT OF COLUMN SPIRALS DO NOT INCLUDE SPLICES OR SPACERS.  
REINFORCING STEEL (GRADE 60) = FY 60,000 PSI.



BENDING DIAGRAMS

SHEET NO. 6 OF 6.

PLATTE COUNTY

A11593